

Oxy9Wave

The Most Accurate Oximeter

High Performance

- * 3.2" Color TFT LCD for Clear View
- * Large memory : Up to 30 Days in 10 Secs
- * Nellcor compatibility

User Convenience

- * Vertical & horizontal display of measurement value
- * Intuitive operation



Vertical display



Horizontal display

SPECIFICATIONS

■ Performance	
SpO₂ (Blood oxygen saturation)	Range : 40 to 100% Accuracy : 70~100%, ±2% 0~69% Unspecified
BPM (Heartbeat)	Range : 30 to 250 bpm Accuracy : ±2bpm
Trend	Memory : 30 days at 10 second interval
■ Display	
Type	3.2" TFT LCD (Resolution : 240 × 400 pixel)
Display parameter	SpO ₂ , BPM, SpO ₂ limit, BPM limit, Level Bar, Heartbeat wave, Time and Date, Alarm volume, Battery status and brightness
LED Display	Sensor separation, Alarm silence, Charging status and Power connection
■ Power Supply	
Power consumption	24VA (max)
Adaptor	Input : 100-240V~, 50-60Hz, 0.4A Output : +5V, 2.0A
Battery	Type : Lithium-ion battery 4400mAh, 3.7V Operating time : Up to 20 hours Charging time : 6.5 hours
■ General	
Operating temperature	5°C to 40°C
Non-operating temperature	-20°C to 70°C
Humidity	5% to 95%
Operating altitude	-1,000 ft to 12,000 ft
Weight	300g
Size	45(H) × 210(W) × 75(D)mm
■ Accessory	
Standard	Adult reusable SpO ₂ finger sensor 1ea AC adaptor 1ea Pole mount bracket 1ea
Option	Neonate reusable SpO ₂ finger sensor (Y-type) Extension cable



Main office: Bionet Co., Ltd.
Tel.: +82-70-7585-6418 (Int'l)
E-mail: sales@ebionet.com (Int'l)

Web: www.ebionet.com
Tel.: 02-6300-6477 (Domestic)
E-mail: yunms@ebionet.com (Domestic)



Delrus Europe Kft.
Allee Corner Business Center
Corner Tower, 4th floor
Hungary, 1117 Budapest, Október 23. utca 8-10.

Tel.: +36 1 882-3579
Fax: +36 1 882-3501
E-mail: delrus.e@delruseurope.com
Web: www.delruseurope.com